



ORDER NO.U2 CODE NO.1022-001



For grinding HSS and carbide engraving cutter as well as single lip or multiple lip cutters of various shapes such as radiused cutters or negative taper angle of cutters. The universal index head is provided at 24 positions so that any particular angle or shape can be obtained, free 3600 or 100 rotation is allowed for grinding End Mills. Twist Drill. Lathe Tools, only replace the attachment to the index head without any complex setup.

※Please confirm voltage & phase when order.

Technical Data

Max. Collet capacity Ø18mm
 Max. Grinding dia. Ø25mm
 Taper angle 0°-180°
 Relief angle 0°-45°
 Negative angle 0°-26°
 Grinding spindle 3600 r.p.m.
 Cup grinding wheel 100x50x20mm
 Motor 1/3Hp 220V50/60Hz, please notify volt & phase
 Net weight 45kgs
 G.W.: 58kgs
 Machine dimensions (LxWxH) 45x40x35cm
 Packing Dimensions (LxWxH) 55x45x47cm

Standard Accessory Included

- Wheel dresser with diamond..... 1pc
- Wheel flange (mounted)..... 1pc
- Grinding wheel (stone)..... 1pc (U2-G)
- Collet Ø4, 6, 8, 10 12mm..... 5pc
- Aligning finger..... 1pc
- Drive belt (U2-B)..... 1pc (U2-B)
- Lock pin..... 1pc
- Tools..... 1set

ENGRAVING AND MILLING CUTTER PROFILES SAMPLE

